

WIBERVA  HOLZ

Solid Wood Panels European Wild Oak

Solid Wood Panels European Wild Oak



European Wild Oak Select (A/B) with continuous lamellas

A-side homogenous panel appearance through optical sorting technology
finely knotty lamella type with pin knots, tight clusters of knots, knobs and sound ingrown knots of maximum 20mm
closed surface
ray flecks permitted

B-side colour variations of the individual lamellas permitted
sporadically occurring cracks permitted
sapwood permitted
ray flecks permitted
sporadically occurring pith permitted

European Wild Oak Select (A/B) with finger-jointed lamellas (only upon request)

A-side homogenous panel appearance through optical sorting technology
sound ingrown knots of maximum 20 mm permitted
closed surface
sporadically occurring pin knots and knobs permitted
sporadic ray flecks permitted
sporadic minimal edge sapwood permitted

B-side colour variations of the individual lamellas permitted
sporadically occurring cracks permitted
sapwood permitted
ray flecks permitted
sporadically occurring ingrown bark permitted

Technical Properties

Adhesive Bonding formaldehyde-free with PVA glue
gluing standard D3 with PVA glue
gluing standard D4 upon request
(above adhesive bonding types are according to German standard DIN EN 204)

Finger Jointing closed surface joint not visible
concealed edge finger jointing

Wood Moisture Content 8% +/- 2%

Surface sanded with grit 80

Lamella Width for continuous lamellas:
46–52 mm uniform within panel
for finger-jointed lamellas:
40–70 mm uniform within panel