



WIBERHA  HOLZ



Stair Tread and Stair Stringer Panels with Continuous Lamellas

Stair Tread and Stair Stringer Panels with Continuous Lamellas



Wood Species:	Maple, Beech steamed, Heartwood Beech steamed, Oak, Ash, Heartwood Ash
Thickness:	40 mm standard thickness 45 mm and special thicknesses upon request
Width:	650 mm or 1300 mm
Stair Tread Length:	900 mm, 1000 mm, 1100 mm, 1200 mm, 1300 mm, 1400 mm, 1500 mm, 1600 mm, 1700 mm, 1800 mm, 1900 mm, 2000 mm
Stair Stringer Length:	2250 mm, 2450 mm, 2750 mm, 3000 mm, 3250 mm, 3500 mm, 3750 mm, 4000 mm, 4250 mm, 4500 mm
Lamella Width:	42–51 mm uniform within panel 48 mm standard width

GRADES

Select:	high quality A/B type
Topside:	<ul style="list-style-type: none">• principally without knots, heartwood and colour streaks• typical wood knots permitted• homogenous panel appearance through optical sorting technology
Underside:	knots, sapwood and heartwood content permitted
Natur:	type includes all typical wood characteristics such as knots, greenish discolouration, and sapwood
Certification:	FSC upon request
Adhesive Bonding:	D3 D4 upon request
Surface:	sanded with grit 80
Wood Moisture Content:	8–10 %