

Solid Wood Panels European Cherry

### Solid Wood Panels European Cherry







## European Cherry Steamed Select (A/B) with continuous lamellas

**A-side** homogenous panel appearance through

optical sorting technology

sporadically occurring pin knots permitted sporadically occurring edge sapwood permitted sporadic green colour variations permitted

**B-side** colour variations of the individual lamellas

permitted

sporadically occurring sound ingrown knots,

black knots and knobs permitted

sapwood permitted

# European Cherry Steamed Select (A/B) with finger-jointed lamellas

**A-side** homogenous panel appearance through

optical sorting technology

sporadically occurring pin knots permitted sporadically occurring edge sapwood permitted sporadic green colour variations permitted

**B-side** colour variations of the individual lamellas

permitted

sporadically occurring sound ingrown knots,

black knots and knobs permitted

sapwood permitted

### Natural Grades (B/C)

**B-side** colour variations of the individual lamellas

permitted

sporadically occurring sound ingrown knots

and black knots permitted

heartwood discolouration permitted

ingrown bark permitted

**C-side** no special requirements, includes all

typical wood characteristics

flawlessly glued

#### **Technical Properties**

Adhesive Bonding formaldehyde-free with PVA glue gluing standard D3 with PVA glue gluing standard D4 upon request

(above adhesive bonding types are according

to German standard DIN EN 204)

Finger Jointing closed surface joint not visible

concealed edge finger jointing

**Wood Moisture** 

**Content** 8 % +/- 2 %

Surface sanded with grit 80

**Lamella** for continuous lamellas:

Width 46–52 mm uniform within panel

for finger-jointed lamellas: 40–70 mm uniform within panel



