



Solid Wood Panels with Continuous Lamellas

## Solid Wood Panels with Continuous Lamellas



Wood Species:	Maple, Acacia steamed,	GRADES	
	Birch, Pear,		
	Beech steamed,	Select:	high quality A/B type
	Heartwood Beech steamed,		Topside:
	Oak, Rustic Oak,		<ul> <li>principally without knots</li> </ul>
	Alder, Ash, Heartwood Ash,		<ul> <li>heartwood and colour streaks</li> </ul>
	Cherry Tree, Walnut,		<ul> <li>typical wood knots permitted</li> </ul>
	Hard Maple, Black Cherry,		<ul> <li>homogenous panel appearance</li> </ul>
	Black Walnut		through optical sorting technology
			<ul> <li>Oak, Nut and Cherry contain</li> </ul>
Thickness:	20 mm, 26 mm, 30 mm,		minimal sapwood on topside
	40 mm, 45 mm		Lie deusides
	Special thicknesses upon request		Underside:
			knots, sapwood and heartwood
Width:	10E0 mm standard width		content permitted
width:	1250 mm standard width	Not set	and the state of the state of the state
		Natural:	type includes all typical wood
Length:	1000mm, 1200 mm,		characteristics such as knots, greenish
	1400 mm, 1600 mm,		discolouration and sapwood
	1800 mm, 2000 mm,		
	2250 mm, 2450 mm,	Certification:	FSC upon request
	2750 mm, 3000 mm		
	Special lengths upon request	Adhesive Bonding:	
			D4 upon request
Lamella Width:	44–51 mm uniform within panel		
	49/51 mm standard width	Surface:	sanded with grit 100
		Wood Moisture	
		Content:	8-10 %

WIBEBA-HOLZ Ges.m.b.H A-3250 Wieselburg . Wiener Straße 30a Tel. +43(0)7416/537 78-0 office@wibeba-holz.com www.wibeba-holz.com

