

WIBERHA  HOLZ

Wood Framing for Fire Doors – Door Frame Jointing

Wood Framing for Fire Doors – Door Frame Jointing



| | |
|------------------------------|--|
| Wood Species: | Oak, Red Oak, Beech |
| Thickness: | 45 mm, 55 mm, 60 mm, 65 mm, 70 mm, 80 mm Special thicknesses upon request |
| Panel Width: | 500 mm, 650 mm, 800 mm, 1250 mm Special widths upon request |
| Frame Jointing Width: | 80 mm, 90 mm, 100 mm, 120 mm, 140 mm, 160 mm, 180 mm, 200 mm Special widths upon request |
| Length: | 2250 mm, 3300 mm, 4300 mm, 5300 mm Special lengths up to 6000 mm available |
| Bonding Type: | single-layer upright bonding multi-bondings (2, 3, 4 layers) |
| Type: | finger- jointed finger-jointed with continuous edge lamella with continuous lamellas |

| | |
|-------------------------------|---|
| Lamella Width: | finger-jointed 20–27 mm finger-jointed with continuous edge lamella: 20–27 mm with continuous lamellas: 46–51 mm |
| Grades: | A/A high quality type for visible application no sapwood, healthy knots up to 5 mm permitted B/B wood finish recommended sapwood, colour streaks and heartwood permitted, healthy knots up to 5 mm permitted |
| Certification: | FSC upon request |
| Adhesive Bonding: | D4 |
| Surface: | sanded with grit 100 |
| Wood Moisture Content: | 8–10 % |